



> Description

The At-Seat-Power series is a range of medium power inverters that provide a 230Vac true sinewave output with very low distortion. Designed for connection directly to the train auxiliary supply, the inverters incorporate surge and transient filtering ensuring compliance with both the traditional and latest rail specifications and norms for protection and EMC. The rugged construction and various mounting options ensure compliance with vibration and shock requirements.

Special features include:

- True sinewave output
- Idea for mobile phone and laptop charging
- Very low distortion
- Low profile for behind seat mounting
- IP65 rated main enclosure
- RCBO output protected behind lockable access door.

> Input Specifications

The following input voltages versions are available as standard:

110V	(66.0 - 137.5V)	dc	(Suffix A)
72V	(43.2 - 90.0V)	dc	(Suffix D)
52V	(31.2 - 65.0V)	dc	(Suffix C)
36V	(21.0 - 50.4V)	dc	(Suffix F)
24V	(16.8 - 33.6V)	dc	(Suffix B) (24V version de-rated to 600W)

Other ranges are available to order



Parameter	Detail
Input Ripple	To RIA 13 and EN50155
Input Protection	Reverse polarity protection via shunt diode that will trip an external circuit breaker. Surges and transients EN50155
Inrush Current	5 x nominal current (after 0.1ms)
Efficiency	85% typically

> Output Specifications

Parameter	Detail
Maximum Output Power	750W continuous (800W peak for 15 seconds)
Output Voltage	230Vac
Setting Tolerance	±1% at 50% load, 15°C to 25°C
Output frequency	50Hz
Frequency Tolerance	±2%
Waveform	True Sinewave
Harmonic Distortion	<6%
Output Current	Nominal 3.3 Amps
Line & Load Regulation	±4.0% combined
Temperature Coefficient	<0.02% / °C
Output Ripple	Typically 5% Pk-Pk of Output Voltage
Short circuit protection	Operates instantaneous if output exceeds 10A (typically). Auto recovery.
Overload protection	Inverter shuts down if output power exceeds approximately 800W for longer than 16 to 20 seconds. LED indications provided. Resets automatically after approximately 10 seconds.
Earth leakage protection	MCBO (combined RCD and circuit breaker) also allows physical isolation of output
Isolation	Input to Output 1.0kV ac (tested at 1.5kV dc) Input to Case 1.0kV ac (tested at 1.5kV dc) Output to Case 1.0kV ac (tested at 1.5kV dc) Relay Contacts 1.0kV ac
Indicators & signalling	Input present Green LED Output present Green LED Overload trip Red LED





> Environmental Details

Parameter	Detail
Operating Temperature	-25°C to +55°C (no derating)
Storage Temperature	-40°C to +80°C
Cooling	By convection
Relative Humidity	95% max.
Shock & Vibration	EN 50155 (EN 61373), RIA 20
Environmental Protection	IP65

> Applicable Norms

Parameter	Detail
EMC	RIA 12, 18; EN50155 (2007), EN50121-3-2 (2006)
Other	RIA 13, 18, 20 EN50155 (2007)

> Mechanical Characteristics

Parameter	Detail
Construction	Fully enclosed in sealed aluminium case
Dimensions	L = 500 mm (includes mounting plate) W = 240 mm H = 125 mm
Weight	<6kg
Connections	M5 studs within the main enclosure accessible via cable glands
Fixings	See below for guidance.

