

## STDA63 SERIES



## 63W Desktop Power Supply for I.T. Equipment

- Wide Input Voltage 90 to 264 VAC, 47 to 63Hz
- IEC-320-C14 input inlet
- Output Voltage Available From 12VDC Thru 50VDC
- Splash Proof
- Class I Insulation
- Input Surge Current, Over Voltage, Over Load and Output Voltage protection.
- Altitude:0-10,000 feet
- CEC Level V, Energy Star 2.0,and RoHS compliance

**2 Year Warranty**

Approvals:          

### Single Output

Product Number	Output Voltage	Output Current	Total Regulation	Maximum Output Power
STDA63-S05	12 ~ 14 VDC	4.75 ~ 4.07 A	5%	57W
STDA63-S06	15 ~ 16 VDC	4.20 ~ 3.94 A	5%	63W
STDA63-S07	16 ~ 21 VDC	3.94 ~ 3.00 A	5%	63W
STDA63-S08	21 ~ 27 VDC	3.00 ~ 2.33 A	5%	63W
STDA63-S09	27 ~ 33 VDC	2.33 ~ 1.91 A	5%	63W
STDA63-S10	33 ~ 40 VDC	1.91 ~ 1.58 A	3%	63W
STDA63-S11	40 ~ 50 VDC	1.58 ~ 1.26 A	3%	63W

Total Regulation is conditioned by below configuration  
(S05: AWG16/4FT output cable)

### Electrical Characteristics

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Input Voltage	Operating Voltage	90		264	VAC
Input Frequency		47		63	Hz
Output Power Range	Vin=90 to 264VAC	0		63	W
Input Current (Low Line)	Io=Full load, Vin=115VAC			1.6	A
Input Current (High Line)	Io=Full load, Vin=230VAC			0.7	A
Low Line Inrush Current	Io=Full load, 25°C ,Cool start, Vin=115VAC		31	35	A
High Line Inrush Current	Io=Full load, 25°C, Cool start, Vin=230VAC		62	70	A
Efficiency	Io=Full Load, Vin=230VAC	84	88	91	%
Line Regulation	Io=Full Load		0.5	1	%
Load Regulation	Vin=230VAC		3	5	%
Over Voltage Protection		112		132	%
Over Current Protection		110		150	%
Transient Response	Io=Full Load to Half Load, Vin=100VAC			4	mS
Hold-Up Time	Io=Full Load, Vin=110VAC	16			mS
Start Up Time	Io=Full Load, Vin=100VAC	0.3	1	2	S
Ripple & Noise (Peak to Peak)	Full Load, Vin=90VAC		0.5	1	%
Safety Ground Leakage Current	Io=Full Load, Vin=240VAC		0.5	0.75	mA
Temperature Coefficient	All output	-0.04		0.04	%/°C
No-Load Power Consumption	No load, Vin=240VAC	0.1		0.5	W



## Conditions

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Operating Temperature		0	40	70	°C
Storage Temperature		-40		85	°C
Relative Humidity		5		95	%
Operation temperature at 25°C, calculated per MIL-HDBK-217F		0.1M			Hrs
Derate linearly from 100% load at 40°C to 50% load at 70°C					

## Approvals and Compliance

Parameter	Test Conditions	Min.	Unit
Dielectric Withstanding Voltage for Primary to secondary	Primary to secondary	4242	VDC
Dielectric Withstanding Voltage for Primary to Ground	Primary to ground	2121	VDC
Isolation Resistance	Test Voltage = 500VDC	50	MΩ
EMI requirements for CISPR-22	Vin=220VAC	B	CLASS
EMI requirements for FCC PART-15	Vin=110VAC	B	CLASS

## Mechanical and PIN out



**Note:**

1. Dimensions are shown in mm & inch
2. Weight: 340gs approx.  
(Exclude the input cord)
3. Optional output connector.