

STUA250 SERIES



250W U-Bracket Power Supply for I.T. Equipment

- Wide Input Voltage 100 to 240 VAC, 47 to 63Hz,
- Output Voltage Available 12, 24, 48VDC
- Internal EMI filter
- Active Power Factor Correction
- Zero Voltage Switching (ZVS) & High Efficiency Up to 93%
- Dimensions: 4.18" x 6." x 1.54"
- Input connector mates with DINKLE#DT-2G-B01W-02P and DINKLE#ESK750V-02P.
- Output connector mates with DINKLE#DT-2G-B01W-(04P or 06P) and DINKLE#ESK750V-(04P or 06P).
- Input Surge Current, Over Voltage and Over Load Protection
- Single Output
- Class I

2 Year Warranty

Approvals:     

Single Output

Product Number	Output Voltage	Max. Output Current	Total Regulation	Maximum Output Power
STUA250-S05	12 VDC	18.33 A	5%	220W
STUA250-S08	24 VDC	10.42 A	3%	250W
STUA250-S11	48 VDC	5.21 A	2%	250W

Electrical Characteristics

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Input Voltage	Operating Voltage	100		240	VAC
Input Frequency		47		63	Hz
Power Factor Correction	Io = Full load, Vin = 90-260VAC	0.95	0.97	1.0	
Output Power Range	Vin=100 to 240VAC	0		250	W
Input Current (Low Line)	Io=Full load, Vin=115VAC			3.3	A
Input Current (High Line)	Io=Full load, Vin=230VAC			1.23	A
Low Line Inrush Current	Io=Full load, 25°C, Cool start, Vin=115VAC		22	25	A
High Line Inrush Current	Io=Full load, 25°C, Cool start, Vin=230VAC		46	50	A
Efficiency	Io=Full Load, Vin=230VAC	89	91	93	%
Line Regulation	Io=Full Load		0.5	1	%
Load Regulation	Vin=230VAC		3	5	%
Over Voltage Protection		112		132	%
Over Current Protection		110		150	%
Transient Response	Io=Full Load to Half Load, Vin=100VAC			4	mS
Hold-Up Time	Io=Full Load, Vin=110VAC	20			mS
Start Up Time	Io=Full Load, Vin=100VAC	0.3	1	2	S
Ripple & Noise (Peak to Peak)	Full Load, Vin=90VAC		0.5	1	%
Safety Ground Leakage Current	Io=Full Load, Vin=240VAC		0.5	0.75	mA
Temperature Coefficient	All output	-0.04		0.04	%/°C

Conditions

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Operating Temperature		0	50	70	°C
Storage Temperature		-40		85	°C
Relative Humidity		5		95	%
Operating Temperature at 25°C, Calculated per MIL-HDBK-217F		0.1M			Hrs
De-rate linearly from 100% load at 50°C to 50% load at 70°C					

Approvals and Compliance

Parameter	Test Conditions	Min.	Unit
Dielectric Withstanding Voltage for Primary to secondary	Primary to secondary	4242	VDC
Dielectric Withstanding Voltage for Primary to Ground	Primary to ground	2121	VDC
Isolation Resistance	Test Voltage=500VDC	50	MΩ
EMI requirements for CISPR-22	Vin=220VAC	B	CLASS
EMI requirements for FCC PART-15	Vin=110VAC	B	CLASS

Mechanical

PIN CHART

MODEL \ PIN	1	2	3	4
STUA250-SXX-4pin	RTN	RTN	OUT	OUT

MODEL \ PIN	1	2	3	4	5	6
STUA250-SXX-6pin	RTN	RTN	RTN	OUT	OUT	OUT

Note:

1. Dimensions are shown in inches or mm.
2. Weight: 790gs approx.
3. Input connector mates with INKLE#DT-2G-B01W-02P and DINKLE#ESK750V-02P.
4. Output connector mates with DINKLE#DT-2G-B01W-(04P or 06P) and DINKLE#ESK750V-(04P or 06P).

