

## ILPA150VW SERIES



## 150W Water-Proof Constant Voltage LED Driver

- Wide Input Voltage 90 to 264VAC, 47 to 63Hz
- Constant Output Voltage Available From 12VDC To 105VDC
- Over Voltage, Over Current, Short Circuit, and Over Temperature Protection
- High Efficiency (up to 94%)
- Active Power Factor Correction (PFC) (99% typical)
- IP67 Waterproof Rating, Metal Housing
- Comply with UL8750 & EN61347 Safety Regulation (Pending)

2 Year Warranty

Approvals:    IP67 

### Single Output

Part Number	Output Voltage	Max. Output Current	Efficiency (220VAC, Full Load)	Over Voltage Protection Min / Typ / Max	Max. Output Power
ILPA150VW-S012ST	12 VDC	12.5 A	92%	14V / 15V / 16V	150W
ILPA150VW-S024ST	24 VDC	6.25 A	93%	27V / 30V / 34V	150W
ILPA150VW-S036ST	36 VDC	4.17 A	93%	40V / 43V / 48V	150W
ILPA150VW-S042ST	42 VDC	3.75 A	94%	45V / 50V / 53V	150W
ILPA150VW-S048ST	48 VDC	3.57 A	93%	47V / 51V / 55V	150W
ILPA150VW-S050ST	50 VDC	3.13 A	93%	54V / 58V / 61V	150W
ILPA150VW-S052ST	52VDC	3.00A	93%	56V / 60V / 63V	150W
ILPA150VW-S054ST	54 VDC	2.88 A	93%	58V / 62V / 66V	150W
ILPA150VW-S056ST	56 VDC	2.78 A	93%	60V / 65V / 69V	150W
ILPA150VW-S081ST	81 VDC	1.85 A	94%	91V / 95V / 100V	150W
ILPA150VW-S105ST	105 VDC	1.42 A	94%	118V / 128V / 135V	150W

### Electrical Characteristics

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Input Voltage	Operating Voltage	90		264	VAC
Input Frequency		47		63	Hz
Output Power Range	Vin=90 to 264VAC	0		150	W
Input Current (Low Line)	Io=Full load, Vin=115VAC			1.75	A
Input Current (High Line)	Io=Full load, Vin=230VAC			0.8	A
High Line Inrush Current	Io=Full load, 25°C, Cool start, Vin=230VAC			50	A
Power Factor Correction	Vin=110VAC		99		%
Power Factor Correction	Vin=220VAC		96		%
Efficiency	Io=Full Load, Vin=230VAC	93		94	%
No-Load Power Consumption	No Load, Vin=230VAC			1.5	W
Line Regulation	Io=Full Load			1	%
Load Regulation	Vin=230VAC			2	%
Over Voltage Protection	Latch mode. The power unit shall return to normal operation only after the power is turn-on again.				
Over Current Protection		110	135	180	% Io
Over Temperature Protection			110		°C
Short Circuit Protection	No damage shall occur when any output operating in a short circuit condition. Self-recovery.				
Output Overshoot / Undershoot	When power on or off			10	%
Start Up Time	Io=Full Load, Vin=100VAC			3	S
Ripple & Noise (Peak to Peak)	Measured by 20 MHz bandwidth oscilloscope and the output paralleled a 0.1 uF ceramic capacitor and a 10 uF electrolytic capacitor.			2	% Vo

## Conditions

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Operating Temperature	Humidity: 10% RH to 100% RH	-35		70	°C
Storage Temperature	Humidity: 5% RH to 100% RH	-40		85	°C
Operation temperature at 25°C, calculated per MIL-HDBK-217F		0.45M			Hours
Life Time at 25°C ambient temperature		0.1M			Hours
No output power derating from -35°C to 65°C					

## Approvals and Compliance

Parameter	Standards
EMI	EN55015
EMS	EN61000-3-2, EN61000-3-3, EN61000-4-2, EN61000-4.3, , EN61000-4-4, , EN61000-4-5, EN61000-4-6, EN61000-4-8, EN61000-4-1-1, EN61547
Safety UL/c-UL, CE	UL8750 Compliant to UL1310 Class 2, UL1012, UL935, CSA-C22.2 No. 0, CSA-C22.2 No. 107.1, CSA-C22.2 No.250.0, EN61347-1,EN61347-2-13
Waterproof	IP67 Rating

## Mechanical

Parameter	Specification
Dimension	199x67.5x40 mm (7.83x2.66x1.57 inches)
Net Weight	1000g approx.

